Lithium-ion batteries for communication backup power








Introduction

Allgrand 48V series lithium iron phosphate battery pack was developed for communication security. Systematically using environmental friendly lithium iron phosphate battery, equipped with high-performanced BMS to effectively manage the battery cells, and has more extensive performance and application advantages compared with traditional batteries.

Widely used in communication base stations, intelligent computer rooms, public security monitoring and other fields, product advantage intelligent centralized monitoring, standardized cabinet installation, integration, light weight, energy saving and environmental protecting.

Appearance





Product features

- Collect battery data in real time
- Statistics related to the working state of power
- Complete power protection function
- Maintainability and Good scalability


Certificates

- ☑ ISO9001:2015
- ☑ ISO14001:2015
- ☑ ISO45001:2018
- ☑ YD/T 2344.1-2011
- ☑ IATF16949:2016
- ☑ GB/T29490-2013
- ☑ GB/T31467.3-2015
- ☑ QB/T2947.3-2008

Technical Parameters

| Types | Basic parameters | AL4810 | AL4850 | AL48100 |
|-----------------------|-----------------------------|--|---------------|---------------|
| Nominal parameters | Nominal Voltage | 48V | 48V | 48V |
| | Nominal Capacity | 10Ah | 50Ah | 100Ah |
| Structural parameters | Size (mm) | 482*260*44 | 482*405*133 | 482*490*222 |
| Electrical parameters | Charge Upper Limit Voltage | 52.5V(15*3.5) | 52.5V(15*3.5) | 52.5V(15*3.5) |
| | Discharge end voltage | 38V | 38V | 38V |
| | Maximum charging current | 5A | 25A | 50A |
| | Maximum discharging current | 10A | 50A | 100A |
| Other parameters | Communication interface | RS232/RS485/CAN | | |
| | operating temperature | -20°C~60°C | | |
| | Storage time | Power off once every 3 months after shutdown | | |
| | Cycle life | ≥3000 (80%DOD) | | |

Note: Data contained herein are measured at 25°C






Lithium-ion batteries for communication backup power






Performance







Temperature Vs. SOC curve 65 60 45 40 0 10 % 20% 30 % 40% 50 % 60% 70% 80% 90% 100% Temperature (C)

Cycle life curves (Different temperature) 100% SOC(%) 90% 80% 70% 60% 50% LiFePO₄ 40% 30% 20% NCM 10% 0% 1000 2000 3000 4000 5000 6000

Applications







DOD(%)

Smart Service Room

Base Station

Data Center

SINCE 1987

Disclaimer: All data presented above are subject to change without further notice.

Please contact ALLGRAND for latest updates.